

1. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a first member having a pivot, and configured to be anchored to the bone;

a second member releasably secured to the first member; and

a cut guide member releasably secured to the second member such that the cut guide member and the second member move together about the pivot of the first member when said second member is selectively released from said first member, wherein said cut guide member is further secured to said second member such that when the cut guide member is selectively released from said second member the cut guide member is thereby permitted to move with respect to said first member independently from said second member;

whereby a surgeon selectively adjusts the device, prior to committing to a cut in the bone, in both a rotational and translational manner while at least a portion of the device is anchored to the bone.

2. (original) The orthopedic cutting guide device of claim 1, wherein said device further comprises at least one securing member implanted within and protruding from the bone.

3. (original) The orthopedic cutting guide device of claim 2, wherein the first member is anchored to the bone by the at least one securing member.

4. (original) The orthopedic cutting guide device of claim 1, wherein said device further comprises a boom configured as a reference to aid the surgeon in making an anterior cut in the bone, and further aids in the avoidance of notching the bone.

5. (original) The orthopedic cutting guide device of claim 4, wherein the cut guide member comprises a top surface and a bottom surface, said top surface having an opening therein configured for receiving a portion of the boom.

6. (original) The orthopedic cutting guide device of claim 5, wherein the boom comprises a first end and a second end, the first end of said boom being dimensioned to fit within the opening of the cut guide member and configured and dimensioned to be secured therein.

7. (original) The orthopedic cutting guide device of claim 2, wherein said first member comprises at least one through hole dimensioned for permitting the at least one securing member to pass therethrough.

8. (original) The orthopedic cutting guide device of claim 1, wherein said first member comprises a top surface, a bottom surface, an outer wall, a first end and a second end, said outer wall tapering outwardly from a central reference point toward the first end and the second end.

9. (original) The orthopedic cutting guide device of claim 8, wherein said first end and said second end of said first member each act as the pivot, and are each shaped in a substantially rounded configuration.

10. (original) The orthopedic cutting guide device of claim 9, wherein the tapering of the outer wall of the first member results in a height measured between the top surface and the bottom surface at the central reference point that is greater than a height measured between the top surface and bottom surface at the first end and the second end.

11. (original) The orthopedic cutting guide device of claim 1, wherein said first member comprises a central through hole.

12. (original) The orthopedic cutting guide device of claim 1, wherein said first member comprises a central through hole, a first side and a second side, wherein the first side and the second side each comprise a plurality of protrusions located medially and laterally of the central through hole of the first member for interacting with the second member and the cut guide member.

13. (original) The orthopedic cutting guide device of claim 12, wherein said second member comprises a plurality of through holes, and said cut guide member comprises a plurality of through holes, such that the plurality of protrusions of the first side of the first member are inserted into the plurality of through holes of the second

member, and the plurality of protrusions of the second side of the first member are inserted into plurality of through holes of the cut guide member, to thereby interact with one another during adjustment of the device.

14. (original) The orthopedic cutting guide device of claim 1, wherein said second member comprises a plurality of through holes.

15. (original) The orthopedic cutting guide device of claim 1, wherein said second member comprises a central through hole and at least one through hole located on either side of the central through hole.

16. (original) The orthopedic cutting guide device of claim 1, wherein said second member comprises at least one translational through hole.

17. (original) The orthopedic cutting guide device of claim 16, wherein said second member comprises a first end and a second end, and wherein said at least one translational through hole comprises a plurality of translational through holes, and wherein at least one of the plurality of translational through holes is located near each of the first end and the second end of the second member.

18. (original) The orthopedic cutting guide device of claim 16, wherein said at least one translational through hole comprises a substantially elongated shape.

19. (original) The orthopedic cutting guide device of claim 14, wherein the plurality of through holes comprises a central hole, a plurality of translational through holes, and a plurality of through holes located medially and laterally of said central through hole.

20. (original) The orthopedic cutting guide device of claim 15, wherein the at least one through hole is shaped in a substantially arcuate manner.

21. (original) The orthopedic cutting guide device of claim 1, wherein said second member comprises a first protruding wall and a second protruding wall.

22. (original) The orthopedic cutting guide device of claim 21, wherein said second member further comprises a first side and a second side, wherein said first protruding wall and said second protruding wall both protrude outwardly from the second side of the second member in a substantially orthogonal manner.

23. (original) The orthopedic cutting guide device of claim 22, wherein said first protruding wall and said second protruding wall are shaped in a substantially arcuate manner.

24. (original) The orthopedic cutting guide device of claim 1, wherein said second member comprises a series of markings corresponding to a predetermined angle of rotation of the second member.

25. (original) The orthopedic cutting guide device of claim 1, wherein said cut guide member further comprises a recessed surface and a sidewall defining a recessed area.

26. (original) The orthopedic cutting guide device of claim 1, wherein said cut guide member further comprises an anterior portion and a posterior portion, said anterior portion having an anterior cutting guide and said posterior portion having a posterior cutting guide.

27. (original) The orthopedic cutting guide device of claim 26, wherein said cut guide member further comprises a connecting portion located on the anterior side of the cut guide member, said connecting portion comprising an opening for receiving a boom therein.

28. (original) The orthopedic cutting guide device of claim 12, wherein said cut guide member further comprises a plurality of substantially elongated holes configured for interacting with at least one of the plurality of protrusions.

29. (original) The orthopedic cutting guide device of claim 1, wherein said cut guide member further comprises a plurality of receiving holes, each receiving hole configured for receiving an attachment member therein.

30. (original) The orthopedic cutting guide device of claim 1, wherein the device further comprises an attachment member configured for releasably securing the second member to the first member, whereby the surgeon selectively loosens the attachment member thereby releasing said second member from the first member such that the second member and the cut guide member rotate together about the pivot of the first member.

31. (original) The orthopedic cutting guide device of claim 1, wherein the device further comprises at least one attachment member configured for releasably securing the cut guide member to the second member, whereby the surgeon selectively loosens the at least one attachment member thereby releasing the cut guide member from the second member such that the cut guide member moves in said translational manner independent from both the second member and the first member.

32. (original) The orthopedic cutting guide device of claim 1, wherein the cut guide member further comprises an anterior cutting guide formed in an anterior portion of said cut guide member.

33. (original) The orthopedic cutting guide device of claim 32, wherein the anterior cutting guide slopes downwardly in a proximal to distal direction from a back surface to a front surface of the cut guide member such that a resulting anterior cut is tapered.

34. (original) The orthopedic cutting guide device of claim 32, wherein the anterior cutting guide is formed as a slit in the anterior portion of said cut guide member.

35. (original) The orthopedic cutting guide device of claim 1, wherein the cut guide member further comprises a posterior portion having a posterior cutting guide that is configured and dimensioned as a template for making a posterior cut in the bone.

36. (original) The orthopedic cutting guide device of claim 35, wherein the posterior cutting guide comprises a substantially flat surface that enables a surgeon to place a cutting instrument in contact with the substantially flat surface of said posterior cutting guide, such that a cut that is substantially straight and flat can be made.

37. (original) The orthopedic cutting guide device of claim 35, wherein the posterior cutting guide is a bottom edge of the cut guide member.

38. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member having a pivot, and configured to be anchored to the bone;

a positioning member configured to be releasably secured to the support member; and

a cut guide member configured to be releasably secured to the positioning member, said cut guide member and said positioning member being secured to one



another, such that the cut guide member and the positioning member move together when said positioning member is selectively released from the support member;

whereby a surgeon selectively adjusts the cut guide member and the positioning member in a rotational manner about the pivot of the support member, prior to committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

39. (original) The orthopedic cutting guide device of claim 38, wherein said device further comprises at least one securing member implanted within and protruding from the bone.

40. (original) The orthopedic cutting guide device of claim 39, wherein the support member is anchored to the bone by the at least one securing member.

41. (original) The orthopedic cutting guide device of claim 39, wherein said support member comprises at least one through hole for permitting the at least one securing member to pass therethrough.

42. (original) The orthopedic cutting guide device of claim 38, wherein said support member comprises an outer wall, a first end and a second end, said outer wall tapers outwardly from a central reference point toward said first end and said second end.

43. (original) The orthopedic cutting guide device of claim 42, wherein said first end and said second end of the support member each operate as the pivot, and are each shaped such that a substantially rounded configuration is achieved.

44. (original) The orthopedic cutting guide device of claim 42, wherein the tapering of the outer wall results in a height at the central reference point that is greater than a height at the first end and the second end.

45. (original) The orthopedic cutting guide device of claim 38, wherein said support member comprises a central through hole.

46. (original) The orthopedic cutting guide device of claim 38, wherein said support member comprises a plurality of protrusions located medially and laterally of a central through hole of the support member configured for interacting with the positioning member.

47. (original) The orthopedic cutting guide device of claim 46, wherein said positioning member comprises a plurality of through holes such that the plurality of protrusions of the support member are inserted into the plurality of through holes of the positioning member such that the plurality of protrusions interacts with the plurality of through holes during rotational adjustment of the device.

48. (original) The orthopedic cutting guide device of claim 38, wherein said positioning member comprises a plurality of through holes.

49. (original) The orthopedic cutting guide device of claim 38, wherein said positioning member comprises a central through hole and at least one through hole located on either side of the central through hole on the positioning member.

50. (original) The orthopedic cutting guide device of claim 49, wherein the at least one through hole located on either side of the central through hole is substantially shaped in an arcuate manner.

51. (original) The orthopedic cutting guide device of claim 48, wherein the plurality of through holes comprises a central hole, a plurality of translational through holes, and a plurality of through holes located medially and laterally of said central through hole.

52. (original) The orthopedic cutting guide device of claim 38, wherein said positioning member comprises a first protruding wall and a second protruding wall, and said support member comprises a first end and a second end that each have a substantially rounded configuration.

53. (original) The orthopedic cutting guide device of claim 52, wherein said positioning member further comprises a first side and a second side, wherein said first protruding wall and said second protruding wall protrude outwardly from the second side of the positioning member in a substantially orthogonal manner.

54. (original) The orthopedic cutting guide device of claim 52, wherein said first protruding wall and said second protruding wall are each shaped in a substantially arcuate manner, such that the first protruding wall and the second protruding wall move about the substantially rounded first and second ends of the support member as the device is rotated, moving both the positioning member and the cut guide member together.

55. (original) The orthopedic cutting guide device of claim 52, wherein the positioning member further comprises a plurality of substantially arcuate through holes, said first protruding wall and said second protruding wall are each shaped in a substantially arcuate manner, such that the first protruding wall and the second protruding wall move about the substantially rounded first and second ends of the support member as the device is rotated, moving both the positioning member and the cut guide member together within the confines of the plurality of substantially arcuate through holes.

56. (original) The orthopedic cutting guide device of claim 38, wherein said positioning member comprises a series of markings corresponding to a predetermined angle of rotation of the positioning member.

57. (original) The orthopedic cutting guide device of claim 38, wherein the device further comprises an attachment member configured for releasably securing the positioning member to the support member, whereby the surgeon selectively loosens the attachment member thereby releasing said positioning member from the support member such that the positioning member and the cut guide member rotate together about the pivot of the support member.

58. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member configured to be anchored to the bone;

a positioning member configured to be releasably secured to the support member; and

a cut guide member configured to be releasably secured to the positioning member such that the cut guide member is selectively adjusted by releasing the cut guide member from said positioning member permitting the cut guide member to move independently from said positioning member and said support member;

whereby a surgeon selectively adjusts the cut guide member in a translational manner with respect to said support member and said positioning member, prior to

committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

59. (original) The orthopedic cutting guide device of claim 58, wherein said device further comprises at least one securing member implanted within and protruding from the bone.

60. (original) The orthopedic cutting guide device of claim 59, wherein the support member is anchored to the bone by the at least one securing member.

61. (original) The orthopedic cutting guide device of claim 58, wherein said device further comprises a boom configured as a reference point to aid the surgeon in making an anterior cut in the bone, and further aids in the avoidance of notching the bone.

62. (original) The orthopedic cutting guide device of claim 61, wherein said cut guide member comprises a top surface and a bottom surface, said top surface having an opening therein configured for receiving a portion of the boom.

63. (original) The orthopedic cutting guide device of claim 62, wherein said boom comprises a first end and a second end, the first end of said boom being dimensioned to fit within the opening of the cut guide member.

64. (original) The orthopedic cutting guide device of claim 59, wherein said support member comprises at least one through hole for permitting the at least one securing member to pass therethrough.

65. (original) The orthopedic cutting guide device of claim 58, wherein said support member comprises an outer wall, a first end and a second end, said outer wall tapers outwardly from a central reference point toward said first end and said second end.

66. (original) The orthopedic cutting guide device of claim 65, wherein said first end and said second end are each shaped such that a substantially rounded configuration is achieved.

67. (original) The orthopedic cutting guide device of claim 66, wherein the tapering of the outer wall results in a height at the central reference point that is greater than a height at the first end and the second end.

68. (original) The orthopedic cutting guide device of claim 58, wherein said support member comprises a central through hole.

69. (original) The orthopedic cutting guide device of claim 58, wherein said support member comprises a plurality of protrusions located medially and laterally of a

central through hole of the support member configured for interacting with the cut guide member.

70. (original) The orthopedic cutting guide device of claim 69, wherein said cut guide member comprises a plurality of through holes, and wherein the plurality of protrusions of the support member are inserted into the plurality of through holes of the cut guide member, such that the plurality of protrusions interacts with the plurality of through holes of the cut guide member during adjustment of the device.

71. (original) The orthopedic cutting guide device of claim 58, wherein said positioning member comprises a plurality of through holes.

72. (original) The orthopedic cutting guide device of claim 58, wherein said positioning member comprises at least one translational through hole.

73. (original) The orthopedic cutting guide device of claim 72, wherein said positioning member comprises a first end and a second end, and wherein said at least one translational through hole comprises a plurality of translational through holes; at least one of the plurality of translational through holes being located at the first end and at the second end of the positioning member.

74. (original) The orthopedic cutting guide device of claim 72, wherein said at least one translational through hole comprises a substantially elongated shape.



75. (original) The orthopedic cutting guide device of claim 58, wherein said cut guide member further comprises a recessed surface and a sidewall defining a recessed area.

76. (original) The orthopedic cutting guide device of claim 58, wherein said cut guide member further comprises an anterior portion and a posterior portion, said anterior portion having an anterior cutting guide and said posterior portion having a posterior cutting guide.

77. (original) The orthopedic cutting guide device of claim 76, wherein said cut guide member further comprises a connecting portion located on the anterior side of the cut guide member, said connecting portion comprising an opening for receiving a boom therein.

78. (original) The orthopedic cutting guide device of claim 69, wherein said cut guide member further comprises a plurality of substantially elongated holes configured for interacting with the plurality of protrusions.

79. (original) The orthopedic cutting guide device of claim 78, wherein said support member comprises a pivot, and wherein said cut guide member and said positioning member are secured to one another such that they move together when said positioning member is selectively released from the support member, whereby the

surgeon selectively adjusts the device by moving said cut guide member and said positioning member in a rotational manner about the pivot of the support member, such that the plurality of protrusions slide within the plurality of substantially elongated holes of the cut guide member as said device is adjusted in said rotational manner, prior to the surgeon committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

80. (original) The orthopedic cutting guide device of claim 58, wherein said cut guide member further comprises a plurality of receiving holes, each receiving hole configured for receiving an attachment member therein.

81. (original) The orthopedic cutting guide device of claim 58, wherein the device further comprises at least one attachment member configured for releasably securing the cut guide member to the positioning member, whereby the surgeon selectively loosens the at least one attachment member thereby releasing the cut guide member from the positioning member such that the cut guide member moves in said translational manner independent from both the positioning member and the support member.

82. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member having a pivot, and configured to be anchored to the bone;

a positioning member configured to be releasably secured to the support member such that the positioning member is selectively moved with respect to the support member when said positioning member is released from said support member; and

a cut guide member configured to be releasably secured to the positioning member, said cut guide member and said positioning member being secured to one another such that they move together in a rotational manner about the pivot of the support member when said positioning member is selectively released from said support member, said cut guide member being further secured to said positioning member such that when the cut guide member is selectively released from said positioning member, the cut guide member is permitted to move in a translational manner with respect to the support member and the positioning member;

whereby a surgeon selectively adjusts the device, prior to committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

83. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member having a pivot, and configured for being anchored to the bone;

a cut guide member configured for engaging the support member such that the support member engages at least a portion of the cut guide member; and

a means for attaching the cut guide member to the support member, such that the cut guide member is secured to said means for attaching and is selectively releasable from said means for attaching, thus permitting the cut guide member to move

in a translational manner independent from and with respect to said support member and said means for attaching when said cut guide member is released from said means for attaching;

whereby a surgeon selectively adjusts the device, prior to committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

84. (original) The orthopedic cutting guide device of claim 83, wherein device further comprises a means for rotating said cut guide member and said means for attaching together about the pivot of said support member such that the device is rotationally adjusted.

85. (original) The orthopedic cutting guide device of claim 84, wherein said means for rotating comprises an attachment member configured for releasably securing the means for attaching to the support member, whereby the surgeon selectively loosens the attachment member thereby releasing said means for attaching from the support member such that the means for attaching and the cut guide member rotate together about the pivot of the support member.

86. (original) The orthopedic cutting guide device of claim 83, wherein said means for attaching further comprises a first protruding wall and a second protruding wall, and a plurality of substantially elongated through holes.

87. (original) The orthopedic cutting guide device of claim 83, wherein said device further comprises at least one attachment member configured to secure the means for attaching to the cut guide member, and wherein said means for attaching comprises at least one translational through hole for receiving the at least one attachment member therethrough, whereby the surgeon selectively loosens the at the least one attachment member, thus releasing the cut guide member from the means for attaching and enabling the cut guide member to move in said translational manner.

88. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member having an outer surface defining the shape of the support member and a pivot located thereon, the support member configured for being anchored to the bone;

a positioning member configured for being secured to the support member, such that the positioning member is selectively releasable from the support member; and

a means for translating the device with respect to the support member, said means for translating configured to be attached to the positioning member such that the means for translating is selectively released from the positioning member permitting the means for translating to move independently from the support member and the positioning member;

whereby a surgeon selectively adjusts the device, prior to committing to a cut in the bone, while at least a portion of the device is anchored to the bone.

89. (original) The orthopedic cutting guide device of claim 88, wherein said device further comprises a means for rotating, which permits the positioning member to rotate about the pivot of the support member to adjust the device in a rotational manner.

90. (original) The orthopedic cutting guide device of claim 88, wherein said means for translating comprises at least one wall surface partially defined by a sidewall, said at least one wall surface defining a translation area wherein the positioning member resides, said translation area having an anterior border and a posterior border providing the limits within which the positioning member moves in an anterior or posterior direction to thereby translate the device relative to said support member.

91. (original) The orthopedic cutting guide device of claim 88, wherein the device further comprises an attachment member configured to attach the means for translating with the positioning member, such that when the attachment member is selectively loosened by the surgeon, the means for translating is released from said positioning member and permitted to move in a translational manner with respect to said support member and said positioning member.

92. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member releasably secured to an end of the bone by a plurality of securing members;

a positioning member releasably secured to the support member; and

SaltLake-281634.2 0040682-00298

23

a cut guide member releasably secured to the positioning member, said cut guide member and said positioning member being secured to one another such that they move together when said positioning member is selectively released from said support member, wherein said cut guide member is further secured to said positioning member, such that when the cut guide member is selectively released from said positioning member the cut guide member is permitted to move with respect to said support member independently from said positioning member;

whereby a surgeon selectively adjusts the device in both a rotational and translational manner with respect to the end of the bone, without reattaching any of the plurality of securing members, prior to committing to a cut in the bone.

93. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member releasably secured to an end of the bone by a plurality of securing members;

a positioning member releasably secured to the support member; and

a cut guide member releasably secured to the positioning member, said cut guide member and said positioning member being secured to one another such that they move together when said positioning member is selectively released from the support member;

whereby a surgeon selectively adjusts the device in a rotational manner with respect to the end of the bone, without reattaching any of the plurality of securing members, prior to committing to a cut in the bone.

94. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member releasably secured to an end of the bone by a plurality of securing members;

a positioning member releasably secured to the support member; and

a cut guide member configured to be releasably secured to the positioning member such that the cut guide member is selectively adjusted by releasing the cut guide member from said positioning member permitting the cut guide member to move independently from said positioning member and said support member;

whereby a surgeon selectively adjusts the device in a translational manner with respect to the end of the bone, without reattaching any of the plurality of securing members, prior to committing to a cut in the bone.

95. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member comprising a pivot, and configured and dimensioned for being secured to an end of the bone;

a positioning member configured and dimensioned for being releasably secured to the support member, and having a first side and a second side, and further having protruding walls that protrude from the second side such that the protruding walls articulate with the pivot of said support member when said positioning member is released from said support member; and



a cut guide member configured and dimensioned for being releasably secured to the positioning member, and having a recessed surface and a sidewall defining a recessed area, said recessed area being dimensioned for receiving therein at least a portion of said support member and said positioning member such that at least a portion of said support member and at least a portion of said positioning member contacts at least one of said recessed surface and said sidewall.

96. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a support member having at least one through hole defined by a sidewall and dimensioned for receiving at least one securing member therethrough such that the support member is secured to an end of the bone;

a positioning member configured for being secured to said support member, and having a top surface and a bottom surface; and

a cut guide member configured for being secured to the positioning member, the cut guide member having a face, and a translation area, the translation area being defined by a wall surface, an anterior border, and a posterior border confining said positioning member such that said positioning member moves freely in an anterior/posterior direction within the translation area until one of the top surface and the bottom surface of the positioning member moves into contact with one of the anterior border and posterior border.

97. (original) An orthopedic cutting guide device for use in resecting a portion of a bone, the device comprising:

a plurality of securing members configured for being inserted into and affixed to the bone;

a support member comprising a central through hole, a first end and a second end each having a substantially rounded configuration and acting as a pivot, the support member further comprising a plurality of through holes configured for permitting the plurality of securing members to pass therethrough, the plurality of through holes of the support member being dimensioned, such that the support member matingly engages and is fixed to the securing members to thereby anchor the device to the bone;

a positioning member comprising a first side, a second side, and a central through hole that is aligned with the central through hole of the support member, the positioning member further comprising at least one translational through hole, and at least one rotational through hole located therein, said positioning member further comprising at least one protruding wall, the at least one protruding wall extending outwardly from the second side of the positioning member in an orthogonal manner, wherein the at least one protruding wall has a substantially rounded configuration such that the at least one protruding wall interacts with and pivots around one of the first end and the second end of the support member, said positioning member configured for being releasably secured to the support member;

a cut guide member comprising a top surface, a bottom surface, and at least one receiving hole located therein that is aligned with the at least one translational through hole of the positioning member, said cut guide member further having a recessed

SeltLake-281834.2 0040682-00298

27

surface and a sidewall defining a recessed area, said cut guide member further comprising a translation area defined by an anterior border, a posterior border, and at least one wall surface that is raised with respect to said recessed surface, said cut guide member further comprising a plurality of through holes configured for permitting the plurality of securing members to pass therethrough and for fitting the cut guide member over the securing members, said cut guide member being releasably secured to the positioning member;

at least one rotational attachment member configured for passing through the central through hole of the positioning member to be received in the central through hole of the support member to thereby secure said positioning member to said support member; and

at least one translational attachment member configured for passing through the at least one translational through hole of the positioning member and being received in the at least one receiving hole of the cut guide member thus securing the cut guide member to the positioning member;

whereby loosening said at least one rotational attachment member releases the positioning member from the support member, such that the positioning member and the cut guide member are selectively rotated together with respect to said securing members; and

whereby loosening the at least one translational adjustment member releases the cut guide member from the positioning member such that the cut guide member is selectively translated with respect to the securing members independent from the support member and the positioning member.

SaltLake-281834.2 0040682-00298

28

98. (original) The orthopedic cutting guide device of claim 97, wherein the device further comprises a boom having a first end and a second end, said boom being configured as a reference for a surgeon's use in making an anterior cut in the bone, and a connecting portion located on the top surface of the cut guide member, said connecting portion having an opening therein that is configured and dimensioned for receiving the first end of the boom.

99-112 (withdrawn)